## NSN 5905-00-100-2014

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-100-2014

-260.0/+260.0  Electrical Resistance:  800.000 ohms  Resistance Tolerance in Percent:  -5.000/+5.000  Ambient Tempurature in Deg Celsius At Full Rated Power:  25.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  275.0  Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius:  -55.0 to 275.0  Tempurature Range Of Tempurature Coefficient in Deg Celsius:  -56.0 to 275.0  Inclosure Method:  Encapsulated  Terminal Type:  Ferrule  Terminal Length:  0.500 inches  Body Diameter:  0.594 inches  Body Length:  1.938 inches  Power Dissipation Rating in Watts:  20.000 free air  Slyle Designator:  Axial terminal each end  Test Data Document:  81349-miliz666 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Na  Unit of Measure:   Demilitarization:  No  Filig:  A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -5.0004-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.50 to 275.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.938 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr 26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Sheft Life: N/a Unit Of Measure:	-260.0/+260.0
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.938 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miltZelic specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Na Unit Of Measure: - Demilitarization: No Filg:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.5094 inches Body Length: 1.338 inches Power Dissipation Rating In Watts: 20.000 free air Sylve Designator: Axial terminal each end Test Data Document: 81349-milt26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	800.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 275.0  Inclosure Method:  Encapsulated  Terminal Type:  Ferrule  Terminal Length:  0.500 inches  Body Diameter:  0.594 inches  Body Length:  1.938 inches  Power Dissipation Rating In Watts:  20.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Inclosure Method: Encapsulated  Terminal Type: Ferrule  Terminal Length: 0.500 inches  Body Diameter: 0.594 inches  Body Length: 1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator: Axial terminal each end  Test Data Document: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0  Inclosure Method: Encapsulated  Terminal Type: Ferrule  Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator: Axial terminal each end Test Data Document: 81349-mill/26/f specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.938 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Diameter: 0.594 inches Body Length: 1.938 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.936 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milir26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	275.0
Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.938 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Ferrule Terminal Length: 0.500 inches Body Diameter: 0.594 inches Body Length: 1.938 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0 to 275.0
Terminal Type: Ferrule  Terminal Length: 0.500 inches  Body Diameter: 0.594 inches  Body Length: 1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator: Axial terminal each end Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Ferrule  Terminal Length: 0.500 inches  Body Diameter: 0.594 inches  Body Length: 1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Terminal Length:  0.500 inches  Body Diameter:  0.594 inches  Body Length:  1.938 inches  Power Dissipation Rating In Watts:  20.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Terminal Type:
0.500 inches  Body Diameter: 0.594 inches  Body Length: 1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Ferrule
Body Diameter:  0.594 inches  Body Length:  1.938 inches  Power Dissipation Rating In Watts:  20.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Terminal Length:
0.594 inches  Body Length: 1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.500 inches
Body Length:  1.938 inches  Power Dissipation Rating In Watts:  20.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
1.938 inches  Power Dissipation Rating In Watts: 20.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fitig:	0.594 inches
Power Dissipation Rating In Watts:  20.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
20.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	1.938 inches
Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document: 81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	20.000 free air
Test Data Document:  81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	81349-milr26/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0