## NSN 5905-00-100-2930

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-100-2930

| Electrical Resistance:  |
|---|
| 10.000 kilohms  |
| Resistance Tolerance In Percent:  |
| -5.000 to 5.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 25.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 275.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0 to 275.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Ferrule   |
| Reliability Indicator:  |
| Not established   |
| Body Diameter:  |
| Between 1.000 inches and 1.312 inches   |
| Body Length:  |
| Between 6.375 inches and 6.500 inches   |
| Power Dissipation Rating In Watts:  |
| 125.000 free air  |
| Cubic Measure (non-core):   |
| 13.396 cubic inches   |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Specification Data:   |
| 81349-mil-r-26/1 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |