NSN 5905-00-100-4049

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-100-4049

4.000 ohms Resistance Tolerance In Percent: -10.000 to 10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator:
-10.000 to 10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
340.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
Encapsulated Terminal Type: Tab, solder lug
Terminal Type: Tab, solder lug
Tab, solder lug
-
Poliobility Indicators
Reliability indicator.
Not established
Terminal Length:
0.562 inches
Body Length:
6.500 inches
Power Dissipation Rating In Watts:
115.000 free air
Err Default:
0.250 inches
Style Designator:
Radial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0