Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-101-1630

Section Quantity:

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.100

Terminal Length:

0.500 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Center To Center Distance Between Terminals:

0.900 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal and unthreaded hole

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0



Center To Center Distance Between Center Terminal And Outside Terminal:

0.700 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39015/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0