

View Online at <https://aerobasegroup.com/nsn/5905-00-101-2198>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.312 inches

Body Diameter:

Between 0.235 inches and 0.265 inches

Body Length:

Between 0.165 inches and 0.195 inches

Shaft Bearing Type:

Sleeve

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

215.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Maximum Stop Torque:

6.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.125 inches

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Rear end

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.011 cubic inches

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

270.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Sealed to permit cleaning in common solvents

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0