

View Online at <https://aerobasegroup.com/nsn/5905-00-102-9612>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Mounting Hole Diameter:

Between 0.075 inches and 0.080 inches

Body Length:

Between 0.370 inches and 0.380 inches

Body Width:

Between 0.180 inches and 0.200 inches

Body Height:

Between 0.370 inches and 0.380 inches

Shaft Bearing Type:

Sleeve

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

Between 6480.0 and 10080.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

Between 0.370 inches and 0.380 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Features Provided:

Humidity proof

Cubic Measure:

0.027 cubic inches

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 6480.0 and 10080.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Sealed to permit cleaning in common solvents

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0