

View Online at <https://aerobasegroup.com/nsn/5905-00-103-3868>

**Section Quantity:**

5

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.8750 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.000 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.500 inches

**Body Length:**

1.480 inches

**Mounting Lip Diameter:**

1.0620 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

340.0

**Maximum Starting Torque:**

1.35 inch-ounces

**Maximum Running Torque:**

1.35 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.0 kilohms 1st section

**Rotary Actuator Travel In Angular Deg:**

340.0

**Function Conformity Tolerance Per Section:**

-0.50 to 0.50 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Terminal Type And Quantity:**

15 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0