NSN 5905-00-103-6460

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-103-6460 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** Between 0.250 inches and 0.375 inches **Body Diameter:** Between 0.240 inches and 0.260 inches **Body Length:** Between 0.219 inches and 0.281 inches **Actuator Type:** Flush drive with slot-hole **Maximum Starting Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 1.000 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 100.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 310.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0 to 250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

65.0 single section

NSN 5905-00-103-6460

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0