# NSN 5905-00-103-7441

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-103-7441

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Rectangular   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.172 inches  |
| Shaft Diameter:   |
| Between 0.050 inches and 0.100 inches                                       |
| Shaft Length:   |
| 0.080 inches  |
| Body Length:  |
| 0.420 inches  |
| Body Width:   |
| Between 0.140 inches and 0.240 inches                                       |
| Body Height:  |
| Between 0.360 inches and 0.390 inches                                       |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Effective Electrical Rotation In Deg Angular Rotation:                      |
| 5400.0 and 10800.0  |
| Center To Center Distance Between Terminals:                                |
| 0.200 inches  |
| Terminal Location:  |
| Rear end  |
| Mounting Method:  |
| Terminal  |
| Electrical Resistance Per Section:  |
| 50.0 ohms single section  |
| Rotary Actuator Travel In Angular Deg:                                      |
| Between 5400.0 and 10800.0  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| Between 0.090 inches and 0.110 inches                                       |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -50.0 to 50.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |

0.75 free air single section

## NSN 5905-00-103-7441

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance | Tolerance | Per | Section | ln | Percent: |
|------------|-----------|-----|---------|----|----------|
|------------|-----------|-----|---------|----|----------|

-5.0 to 5.0 single section

## **Actuator Travel Control Feature:**

Continuous motion

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## **Test Data Document:**

81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

## **Specification Data:**

81349-mil-r-27208/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0