

View Online at <https://aerobasegroup.com/nsn/5905-00-103-7452>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.934 inches

Body Diameter:

0.672 inches

Shaft Diameter:

0.500 inches

Shaft Length:

2.000 inches

Mounting Bushing Length:

0.500 inches

Body Length:

0.734 inches

Body Inside Diameter:

0.076 inches

Overall Diameter:

0.876 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

4.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Maximum Stop Torque:

32.00 inch-ounces

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.234 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms 2nd section

Rotary Actuator Travel In Angular Deg:

260.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0