Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-104-0730

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

5.000 inches

First Flat Length:

1.563 inches

Flat Height:

0.031 inches

Body Diameter:

12.000 inches

Shaft Diameter:

0.375 inches

OI (1)

Shaft Length:

2.000 inches

Mounting Bushing Length:

0.500 inches

Body Length:

3.000 inches

Overall Diameter:

12.000 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Lateral Distance Between Mounting Hole Centers:

6.000 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

NSN 5905-00-104-0730

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 50.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 1000.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0