## NSN 5905-00-104-0730

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-104-0730 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 5.000 inches First Flat Length: 1.563 inches Flat Height: 0.031 inches **Body Diameter:** 12.000 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 2.000 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 3.000 inches **Overall Diameter:** 12.000 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 6.000 inches **Screw Thread Diameter:** 0.250 inches

**Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 20.0 **Mounting Facility Quantity:** 2

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Threaded hole

## NSN 5905-00-104-0730

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Electrical Resistance Per Section: 50.0 ohms single section Power Dissipation Rating Per Section In Watts: 1000.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A002a0