Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-104-0926

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Overall Length:

2.593 inches

Undercut Diameter:

0.750 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

1.875 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

100.00 inch-ounces

AeroBase Group

Precision Nonwire Wound Variable Resistor - Page 2 of 3

Shaft End Play: 0.005 inches Shaft Runout: 0.001 inches Lateral Runout: 0.001 inches **Pilot Diameter Runout:** 0.001 inches Shaft Radial Play: 0.001 inches **Terminal Location:** Rear end **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 3600.0 and 3700.0 **Function Conformity Tolerance Per Section:** -0.075 to 0.075 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 160.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -300.0 to 300.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section graph Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Test Data Document:** 84347-g121-080 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 turret Shelf Life:

N/a

Unit Of Measure:

NSN 5905-00-104-0926

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0