NSN 5905-00-104-7161

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-104-7161 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.297 inches **Terminal Length:** 0.500 inches **Overall Height:** 0.810 inches **Mounting Hole Diameter:** 0.086 inches

Shaft Diameter: 0.125 inches

Shaft Length: 0.047 inches

Body Length: 1.250 inches **Body Width:**

0.250 inches **Body Height:**

0.312 inches **Shaft Style:**

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Maximum Starting Torque:

7.50 inch-ounces

Maximum Running Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.688 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

Terminal Location:

Lower adjacent side single row

NSN 5905-00-104-7161

Precision Wire Wound Variable Resistor - Page 2 of 2



Unthreaded hole Electrical Resistance Per Section: 5.000 kilohms single section 8.000 kilohms single section 9.000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 9.0328 inches 8.000 kilohms single section 1.0328 inches 1.000 kilohms single section 1.000 kilohms sing	
Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: 100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: 100.0/+100.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Wyspecial features for proper functioning of the items Test Data Document: 0.4660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: No/a United Of Measure: ————————————————————————————————————	Mounting Method:
Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 900.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: 100.0/+10.00 single section Power Dissipation Rating Per Section In Watts: 90.8 free air single section Resistance Tolerance Per Section In Percent: 10.0/+10.0 single section Resistance Tolerance Per Section In Percent: 10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 904660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-40 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 104660-400725-40 drawing (this is the basic governing drawing) travelled to the drawing of the items 104660-400725-40 drawing (this is the basic governing drawing) travelled to the drawing of the items 104660-400725-40 drawing (this is the basic governing drawing) travelled to the drawing of the items 10466	Unthreaded hole
Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: 100.0/+10.00 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Wispecial features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure:	Electrical Resistance Per Section:
Center To Center Distance Between Center Terminal And Outside Terminal: 0.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	5.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal: 0.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Wispecial features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/A Unit Of Measure:	Rotary Actuator Travel In Angular Deg:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Center To Center Distance Between Center Terminal And Outside Terminal:
135.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure:	0.328 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Citutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Wyspecial features for proper functioning of the items Test Data Document: 0.4660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	135.0 single section
Power Dissipation Rating Per Section In Watts: 0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
0.8 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	-100.0/+100.0 single section
Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special Features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating Per Section In Watts:
Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	0.8 free air single section
Actuator Travel Control Feature: Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Resistance Tolerance Per Section In Percent:
Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Actuator Travel Control Feature:
70.0 single section Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure:	Clutch
Special Features: W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
W/special features for proper functioning of the items Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	70.0 single section
Test Data Document: 04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure:	Special Features:
04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	W/special features for proper functioning of the items
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	04660-400725-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Reference Number Differentiating Characteristics: As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
As differentiated by navord od41152 Shelf Life: N/a Unit Of Measure: Demilitarization:	3 pin
Shelf Life: N/a Unit Of Measure: Demilitarization:	Reference Number Differentiating Characteristics:
N/a Unit Of Measure: Demilitarization:	As differentiated by navord od41152
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
	
No	Demilitarization:
	No
Fiig:	Fiig:
A002a0	A002a0