NSN 5905-00-105-3444

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-105-3444

-100.0 to 100.0 Electrical Resistance: 150.000 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 185.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.082 inches and 1.625 inches Body Length: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Umpackaged Unit Weight: 0.5 grams Style Designator: Akial terminal each end Tests Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure: — Demilitarization: No Filig:	
Electrical Resistance: 150.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Actal terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shell Life: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Diameter: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.5 of grams Style Designator: Avial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Filig:	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.020 inches and 0.281 inches Power Diasipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
-1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Retiability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.098 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.024 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Welght: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-11820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-1.000 to 1.000
Ambient Tempurature In Deg Ceisius At Zero Percent Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient In Deg Ceisius: -55.0 to 185.0 Inclosure Method: Encapsulated Terminal Type: Wirre Isad Reliability Indicator: Note established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.298 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: Ob. grams Style Designator: Axial terminal each end Test Data Document: Excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inciosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Bedy Dlameter: Between 0.082 inches and 0.098 inches Body Dlameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Unpackaged Unit Welght: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Jameter: Between 0.082 inches and 0.098 inches Body Jameter: Between 0.082 inches and 0.098 inches Body Length: Botween 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	165.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unipackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	-55.0 to 165.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Encapsulated
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Wire lead
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Length:
Between 0.082 inches and 0.098 inches Body Length: Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 1.375 inches and 1.625 inches
Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.204 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.082 inches and 0.098 inches
Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.204 inches and 0.281 inches
Unpackaged Unit Weight: 0.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
O.5 grams Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unpackaged Unit Weight:
Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.5 grams
Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
Fiig:	No
	Fiig:
	A001a0