NSN 5905-00-105-3493

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-105-3493

-100.0/+100.0 Electrical Resistance: 976.000 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -56.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Aktal terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Michael Demilitarization: No Dismilitarization: Domilitarization: Domilitarization: Domilitarization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Akula terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: No Umit Of Measure:	-100.0/+100.0
Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-11820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
-1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.0281 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 0.001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	976.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 155.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 0.001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Tests Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Avail terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.088 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Terminal Type:
Note stablished Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Wire lead
Body Length: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Body Length: 0.0281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
0.281 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.098 inches
Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Oriticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.281 inches
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Style Designator: Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Axial terminal each end Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test
Test Data Document: 10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	10001-1820944 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0