## NSN 5905-00-105-5305

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-105-5305

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.438 inches
Terminal Length:
0.188 inches
Body Diameter:
Between 0.240 inches and 0.260 inches
Shaft Diameter:
0.070 inches
Shaft Length:
0.250 inches
Body Length:
Between 0.250 inches and 0.312 inches
Overall Diameter:
Between 0.240 inches and 0.260 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.195 inches and 0.205 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.095 inches and 0.105 inches
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

## NSN 5905-00-105-5305

Demilitarization:

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
35.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
12498-a42564-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Геrminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
<u>-</u>