

View Online at https://aerobasegroup.com/nsn/5905-00-105-5308

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

**Overall Length:** 

0.438 inches

Terminal Length:

0.188 inches

Body Diameter:

Between 0.240 inches and 0.260 inches

Shaft Diameter:

Between 0.110 inches and 0.120 inches

Shaft Length:

0.420 inches

Body Length:

Between 0.250 inches and 0.312 inches

**Overall Diameter:** 

Between 0.240 inches and 0.260 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

**Center To Center Distance Between Terminals:** 

Between 0.195 inches and 0.205 inches

**Terminal Location:** 

Rear end

**Mounting Method:** 

Terminal

**Electrical Resistance Per Section:** 

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.095 inches and 0.120 inches

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## **Actuator Travel Control Feature:**

Continuous motion

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## Standard Taper Curve Per Section:

A single section

## Test Data Document:

42498-a42564-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A002a0