

View Online at <https://aerobasegroup.com/nsn/5905-00-105-5336>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes

**Reliability Indicator:**

Not established

**Overall Length:**

Between 0.565 inches and 0.815 inches

**Terminal Length:**

Between 0.285 inches and 0.315 inches

**Overall Height:**

Between 0.390 inches and 0.440 inches

**Overall Width:**

Between 0.140 inches and 0.150 inches

**Mounting Hole Diameter:**

0.074 inches

**Shaft Diameter:**

0.115 inches

**Shaft Length:**

Between 0.030 inches and 0.050 inches

**Body Length:**

Between 0.380 inches and 0.400 inches

**Body Width:**

Between 0.140 inches and 0.150 inches

**Body Height:**

Between 0.360 inches and 0.390 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Center To Center Distance Between Terminals:**

Between 0.190 inches and 0.210 inches

**Lateral Distance Between Mounting Hole Centers:**

Between 0.414 inches and 0.424 inches

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Clamp ring and unthreaded hole

**Features Provided:**

Grounded contact arm

**Electrical Resistance Per Section:**

50.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.090 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

175.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0