NSN 5905-00-105-7448

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-105-7448

Electrical Resistance: 15.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
-55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
-55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Not established Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Body Diameter: 0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
0.250 inches Body Length: 1.000 inches Power Dissipation Rating In Watts:
Body Length: 1.000 inches Power Dissipation Rating In Watts:
1.000 inches Power Dissipation Rating In Watts:
Power Dissipation Rating In Watts:
0.750 francis
0.750 free air
Product Name:
Resistor, fixed, wire wound, noninduction
Style Designator:
Axial terminal each end
Test Data Document:
83843-906d725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0