NSN 5905-00-105-7472

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-105-7472

View Online at https://aerobasegroup.com/nsn/5905-00-109
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.300 inches and 1.340 inches
Terminal Length:
Between 0.469 inches and 0.531 inches
Overall Height:
Between 0.779 inches and 0.861 inches
Overall Width:
0.195 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.110 inches
Shaft Length:
Between 0.060 inches and 0.080 inches
Body Length:
Between 1.240 inches and 1.260 inches
Body Width:
0.195 inches
Body Height:
Between 0.310 inches and 0.330 inches
Shaft Style:
Round, slotted
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
Between 0.690 inches and 0.710 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Desistance Der Castian.

20.000 kilohms single section

Electrical Resistance Per Section:

NSN 5905-00-105-7472

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.290 inches and 0.310 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.075 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life: N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0