NSN 5905-00-105-7474

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-105-7474 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** Between 0.485 inches and 0.515 inches **Body Diameter:** 0.310 inches **Body Length:** Between 0.165 inches and 0.195 inches **Contact Arm Electrical Off Position:** Fully cw **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 6.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 2.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 300.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.095 mils and 0.105 centimeters Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

NSN 5905-00-105-7474

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: