Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-105-7518

# Section Quantity:

1

Body Style:

Cylindrical

# Reliability Indicator:

Not established

#### **Body Diameter:**

0.688 inches

#### **Body Length:**

0.344 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Tab

#### **Electrical Resistance Per Section:**

250.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

# **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

# Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

#### **Standard Taper Curve Per Section:**

A single section

# **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5905-00-105-7518

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

