NSN 5905-00-106-5163

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-106-5163 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** Between 0.515 inches and 0.555 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.180 inches and 0.200 inches **Mounting Slot Width:** Between 0.090 inches and 0.096 inches **Shaft Diameter:** Between 0.078 inches and 0.088 inches **Shaft Length:** Between 0.025 inches and 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.490 inches and 0.510 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** Between 0.515 inches and 0.530 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Slot **Electrical Resistance Per Section:** 2.0 kilohms single section

2.0 Kilonms single section

Rotary Actuator Travel In Angular Deg:

9000.0

NSN 5905-00-106-5163

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**