## NSN 5905-00-106-5175

**Section Quantity:** 

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-106-5175

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.594 inches and 1.688 inches
Body Diameter:
Between 1.296 inches and 1.328 inches
Shaft Diameter:
Between 0.406 inches and 0.407 inches
Shaft Length:
Between 0.734 inches and 0.766 inches
Mounting Bushing Length:
Between 0.359 inches and 0.391 inches
Body Length:
Between 0.718 inches and 0.750 inches
Overall Diameter:
1.342 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Single shaft  Effective Electrical Rotation In Deg Angular Rotation:
-
Effective Electrical Rotation In Deg Angular Rotation:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius: Between 0.546 inches and 0.578 inches
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius: Between 0.546 inches and 0.578 inches  Shaft End Play:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius: Between 0.546 inches and 0.578 inches  Shaft End Play: 0.0005 inches
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius: Between 0.546 inches and 0.578 inches  Shaft End Play: 0.0005 inches  Shaft Runout:
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius: Between 0.546 inches and 0.578 inches  Shaft End Play: 0.0005 inches  Shaft Runout: 0.005 inches
Effective Electrical Rotation In Deg Angular Rotation: Between 350.0 and 354.0  Maximum Starting Torque: 0.70 inch-ounces  Maximum Running Torque: 0.50 inch-ounces  Nonturn Device Location: At 6 oclock  Nonturn Device Radius: Between 0.546 inches and 0.578 inches  Shaft End Play: 0.0005 inches  Shaft Runout: 0.005 inches  Lateral Runout:

## NSN 5905-00-106-5175

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft Radial Play:
0.004 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Front end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Single section independent linearity  Resistance Tolerance Per Section In Percent:
Resistance Tolerance Per Section In Percent:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Continuous motion
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear
Resistance Tolerance Per Section In Percent:  -5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section:  Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 3 tab, solder lug
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a  Unit Of Measure:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: