Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-107-0501

# Section Quantity:

1

Body Style:

Rectangular w/bushing

# Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

## Mounting Bushing Length:

0.375 inches

**Body Length:** 

0.700 inches

Body Width:

## 1.230 inches

Shaft Style:

#### Round, slotted

Actuator Type:

## Single shaft

Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.530 inches

## Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

3.000 kilohms single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Standard Taper Curve Per Section:

A single section

#### **Terminal Type And Quantity:**

3 eyelet

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0