NSN 5905-00-107-2621

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-107-2621

| Section Overtitus |
|---|
| Section Quantity: |
| 1 Pade Styles |
| Body Style: |
| Cylindrical Polichility Indicators |
| Reliability Indicator: Not established |
| Overall Length: |
| Between 0.469 inches and 0.655 inches |
| Body Diameter: |
| Between 0.240 inches and 0.260 inches |
| Body Length: |
| Between 0.219 inches and 0.281 inches |
| Overall Diameter: |
| Between 0.240 inches and 0.260 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Effective Electrical Rotation In Deg Angular Rotation: |
| Between 190.0 and 235.0 |
| Terminal Location: |
| Front end |
| Mounting Method: |
| Terminal |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 5.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 308.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| +0.0 to 250.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -20.0 to 20.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| |

A single section

NSN 5905-00-107-2621

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Test Data Document:

13499-381-1740-090 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0