Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-107-4887

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.165 inches

#### Shaft Diameter:

0.095 inches

#### Shaft Length:

0.060 inches

#### **Body Length:**

0.750 inches

#### Body Width:

0.190 inches

## Body Height:

0.250 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

5400.0

#### **Center To Center Distance Between Terminals:**

0.500 inches

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

5.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

5400.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# NSN 5905-00-107-4887 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A002a0