Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-107-8204

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.062 inches

#### Body Diameter:

1.062 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.562 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

#### Nonturn Device Location:

At 3 oclock and at 9 oclock

**Nonturn Device Radius:** 

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

#### **Electrical Resistance Per Section:**

10.000 kilohms single section

### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

#### **Function Conformity Per Section:**

Single section independent linearity



### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0