NSN 5905-00-107-8532

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-107-8532

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.188 inches
Body Diameter:
1.063 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.563 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
Nonturn Device Location: At 3 oclock and at 9 oclock
At 3 oclock and at 9 oclock
At 3 oclock and at 9 oclock Nonturn Device Radius:
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter:
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method:
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section:
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 50.000 kilohms single section
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 50.000 kilohms single section Power Dissipation Rating Per Section In Watts:
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 50.000 kilohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section
At 3 oclock and at 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 50.000 kilohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section Resistance Tolerance Per Section In Percent:

NSN 5905-00-107-8532

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0