NSN 5905-00-108-1096

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-1096

view Online at https://aerobasegroup.com/nsn/5905-00-108-1096
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
1.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.750 inches
Body Length:
0.562 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
150.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
L single section
Special Features:
Clock spring connector between drive arm and center terminal
Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-108-1096

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0