Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-1699

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Overall Length:**

1.313 inches

### **Body Diameter:**

1.063 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.563 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

### Nonturn Device Location:

At 3 oclock and at 9 oclock

#### Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

1.000 megohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0