Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-4605

view Online at https://aerobasegroup.com/nsn/5905-00-106-4605
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 1.609 inches and 1.641 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.547 inches and 0.578 inches
Shaft Style:
Round, slotted, knurled
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
275.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
4.0 ohms single section
Rotary Actuator Travel In Angular Deg:
294.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

## NSN 5905-00-108-4605

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0