NSN 5905-00-108-4634

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-4634 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.156 inches **Body Length:** 1.266 inches **Effective Electrical Rotation In Deg Angular Rotation:** 292.0 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Rotary Actuator Travel In Angular Deg:** 312.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-00-108-4634

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0