NSN 5905-00-108-4669

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-4669 **Section Quantity: Overall Length:** 1.062 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Overall Diameter:** 1.812 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 258.0 **Maximum Starting Torque:** 4.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Lower adjacent side two rows **Mounting Method:** Threaded hole **Features Provided:** Nonmetallic shaft

Electrical Resistance Per Section:

50.000 ohms single section

Rotary Actuator Travel In Angular Deg:

258.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

NSN 5905-00-108-4669

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
6.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0 to 50.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
20.0 single section
Terminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
۸۵۵220