Nonprecision Wire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-108-4954

Section Quantity:
1
Shaft Diameter:
0.250 inches
Shaft Length:
0.562 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.512 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
20:0 to 20:0 billigio bootion
Standard Taper Curve Per Section:
-
Standard Taper Curve Per Section:
Standard Taper Curve Per Section: A single section
Standard Taper Curve Per Section: A single section Terminal Type And Quantity:
Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug
Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life:
Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:
Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: