NSN 5905-00-108-5321

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5321 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 0.438 inches **Mounting Bushing Length:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 20.000 kilohms 2nd section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-00-108-5321

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0