

View Online at <https://aerobasegroup.com/nsn/5905-00-108-5344>

**Section Quantity:**

2

**Reliability Indicator:**

Not established

**First Flat Length:**

0.187 inches

**Flat Height:**

0.216 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.562 inches

**Mounting Bushing Length:**

0.250 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

350.000 kilohms 2nd section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 1st section

**Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:**

Any acceptable

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0