NSN 5905-00-108-5378

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5378 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.250 inches **Terminal Length:** 0.156 inches First Flat Length: 0.344 inches Flat Height: 0.219 inches **Body Diameter:** 1.562 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.375 inches **Overall Diameter:** 1.718 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-108-5378

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0