## NSN 5905-00-108-5411

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5411

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.250 inches
Terminal Length:
0.156 inches
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Body Diameter:
1.562 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.250 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Overall Diameter:
1.718 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing

## NSN 5905-00-108-5411

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



<b>Electrical Resistance Per Section:</b>
175.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0