NSN 5905-00-108-5450

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5450 **Section Quantity: Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 28.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 100.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 16200.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-00-108-5450

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A002a0