NSN 5905-00-108-5455

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5455 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.300 inches **Overall Height:** 0.300 inches **Overall Width:** 0.180 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.050 inches **Shaft Length:** 0.120 inches **Body Length:** 1.250 inches **Body Width:** 0.180 inches **Body Height:** 0.300 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:**

Unthreaded hole **Features Provided:** Nonmetallic shaft

Electrical Resistance Per Section:

1.000 kilohms single section

NSN 5905-00-108-5455

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 7920.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 1 wire loop Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No

Fiig:

A002a0