## NSN 5905-00-108-5588

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5588

view Online at https://aerobasegroup.com/nsn/5905-00-106-5566
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
1.280 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
evaluate commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

## **Terminal Type And Quantity:**

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

3 tab, solder lug

## NSN 5905-00-108-5588

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Demilitarization:

No

Fiig:

A002a0