Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-108-5679

Section	Quantity:

2

- **Reliability Indicator:**
- Not established
- Shaft Diameter:
- 0.250 inches
- Shaft Length:
- 0.625 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Nonturn Device Location:
- At 3 oclock and at 9 oclock
- Nonturn Device Radius:
- 0.531 inches
- Screw Thread Diameter:
- 0.375 inches
- Screw Thread Series Designator:
- Unef
- Screw Thready Qty Per Inch (tpi):
- 32.0
- Mounting Method:
- Locking bushing
- **Electrical Resistance Per Section:**
- 50.0 kilohms all sections
- **Power Dissipation Rating Per Section In Watts:**
- 2.0 free air all sections
- **Resistance Tolerance Per Section In Percent:**
- -10.0 to 10.0 all sections
- Standard Taper Curve Per Section:
- A all sections
- **Terminal Type And Quantity:**
- 6 tab, solder lug
- Shelf Life:
- N/a
- Unit Of Measure:
- ---
- Demilitarization:
- No
- Fiig:
- A002a0