Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5751

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.125 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.312 inches

## Mounting Bushing Length:

0.375 inches

#### Body Length:

## 1.156 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

## Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

1.0 megohms all sections

# Rotary Actuator Travel In Angular Deg:

300.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

# NSN 5905-00-108-5751 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 all sections

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

## Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A002a0