Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5758

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

1.156 inches

## Shaft Diameter:

0.250 inches

#### Shaft Length:

2.000 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

## 1.266 inches

Shaft Style:

## Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

295.0

## Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

200.0 ohms all sections

## Rotary Actuator Travel In Angular Deg:

295.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

# NSN 5905-00-108-5758 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.25 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

## Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A002a0