NSN 5905-00-108-5894

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-5894 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 2.219 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.219 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 250.000 ohms all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 all sections **Power Dissipation Rating Per Section In Watts:** 50.0 free air all sections **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

NSN 5905-00-108-5894

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No