Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-6189

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

1.775 inches

#### Body Diameter:

1.700 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

#### Mounting Bushing Length:

### 0.375 inches

**Body Length:** 

0.900 inches

## Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

10.000 kilohms single section

# Power Dissipation Rating Per Section In Watts:

3.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0