NSN 5905-00-108-6254

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-6254 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 1.625 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Body Length:** 0.625 inches **Overall Diameter:** 1.938 inches **Mounting Hole/stud Circle Diameter:** 1.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 315.0 **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:**

Threaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

5.0 kilohms single section

NSN 5905-00-108-6254

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section Power Dissipation Rating Per Section In Watts: 8.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity:
Power Dissipation Rating Per Section In Watts: 8.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
Power Dissipation Rating Per Section In Watts: 8.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
8.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
-10.0 to 10.0 single section Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
Actuator Travel Control Feature: Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
-20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section
40.0 single section Standard Taper Curve Per Section: A single section
Standard Taper Curve Per Section: A single section
A single section
•
Terminal Type And Quantity:
Terminal Type And adamty.
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0