NSN 5905-00-108-6255

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-6255 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 2.125 inches **Body Diameter:** 2.750 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.000 inches **Body Length:** 1.125 inches **Overall Diameter:** 3.000 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Rear-bottom **Mounting Method:**

Threaded hole

Features Provided:

Nonmetallic shaft

NSN 5905-00-108-6255

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
330.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
0.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0